

Cocoa Mat

Natural Cocoa Fiber Mat

Available 6'7" x 40'

Custom – 6'7" width by custom lengths to 40'

PRODUCT SPECIFICATIONS

PRODUCT COMPOSITION	DATA
Manufacturing Process	Cut Pile
Pile yarn composition	Natural Cocoa Fiber
Primary Backing	Vinyl
Water Absorption	Highly absorbent
PRODUCT DIMENSIONS	
Pile Height	5/8" - .67 inches; 3/4" - .79 inches; 1" - .91 inches
Total Height	5/8", 3/4", 1" (Note: Natural Color Available in 5/8", 3/4" or 1". All other colors 3/4" Only)
Total Weight	5/8" - 166.79 oz/sy; 3/4" -181.36 oz/sy; 1" – 194.64 oz/sy
COLOR FASTNESS	
To Light	When exposed to natural light, the colored goods will fade in direct relationship to the amount of light or sunlight to which it is exposed.
To Water	Approx. 90% return when thoroughly saturated
Shedding	Shedding condition is not a product defect, but common to new mat installations. This condition will be minimal after some use and several vacuuming.

INSTALLATION

Floor area should be completely clean, dry, and free of foreign substances. Use a floor leveler as needed to ensure floor is smooth, even and without cracks. Our matting products can be cut easily to any size, shape or pattern with a utility knife. Follow adhesive manufacture's instructions.

Adhesive: Release-Bond Mat Adhesive, or approved equal.

CLEANING & MAINTENANCE

Daily: Vacuum daily with a commercial grade vacuum cleaner that features a rotary power brush or beater bar. Mats release more soil when completely dry.

Periodic Maintenance: Our matting products clean beautifully with the use of a Hot Water Extraction machine. Minimum quarterly intervals recommended for high traffic applications. For optimum performance during winter months, traffic lanes may require more frequent extraction cleaning depending on weather conditions and climate.

WARRANTY

Limited 3-Year Abrasive Warranty. limited warranty for abrasive wear on indoor installations. Warranty requires product installation over a dry, smooth, hard, flat surface free of cracks and foreign substances. Product must be installed using the appropriate brand adhesive, or approved equal. Product must be maintained according to maintenance instructions.